



Module



WLAN USB module 144 Mbs

Description

The Delock USB module offers in a compact construction WLAN function via USB interface and is ideal for installation in industry components like sensors, IPCs, PDAs or notebooks.



Ref. 95820

EAN 4043619958207

Specification

- USB 2.0 interface
- WLAN according IEEE b/g/n (Draft 2.0)
- Chipset: Ralink RT2770U (2720)
- 2,4GHz
- 11b: 1,2,5.5,11Mbps / 11g: 6,9,12,24,36,48,54Mbps
- 11n: legacy, mixed and green field modes, supports 20/40 MHz band width MCS0- 7 (150Mbps PHY rate support)
- 2 mini coax antenna connection (1T2R)
- Hardware WEP, TKIP, AES engines
- EAP TLS, TTLS, LEAP, PEAP
- WPA1/2 PSK (WPA home)
- WPA1/2 802.1x (WPA enterprise)
- Oposite data fllow, link adaptation, roaming
- Voltage: 5V
- Operating temperature: 0~65°C
- Relative humidity during operation: max.95% (non-condensing)
- Size: 60 x 25 x 3,8mm (LxWxH)
- For Windows CE 5.0 & 6.0/ 98SE/ ME/2000/XP/Vista, Linux2.6x, Mac OS 10.3 & 10.4