



#### NOTES:

##### ELECTRICAL:

1. VOLTAGE RATING : 125V AC RMS
2. CURRENT RATING : 1.5A mp
3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
6. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 C.2

##### ENVIRONMENTAL:

1. STORAGE : -40° TO+85°
  2. OPERATION : 0° TO+70°
- RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5  
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68
- ##### MECHANICAL
1. RJ45 JACK LIFE: 750 TIMES MIN
  2. IDC LIFE : 200 TIMES MIN

#### MATERIAL LIST:

⑦	Upper Panel Cover	1.2mm thickness Metall Panel with plastic powder cladding	1	
⑥	Bottom Panel	1.5mm thickness Metall Panel with plastic powder cladding	1	
⑤	RJ45 Jack	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	12	
④	PCB	1.6mm UL 94V0	2	
③	IDC BODY	Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B	12	
②	IDC PIN	Phosphor Bronze & Tinned	96	
①	IDC TERMINAL	For 22-24 AWG Cable	12	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK



Title: 10" Patch Panel 12 Port Cat.6A  
0.5 U grey

43311

Barcode 4043619433117

File No. 88220