

P1

P2

DB9P FEMALE

DB9P MALE

NOTES:

- 1.ELECTRICAL TEST:100%OPEN,SHORT&MIS WIRE TEST.
- 2.CONDUCTOR RESISTANCE:2 ohm.
- 3.INSULATOR RESISTANCE:5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

PIN WIRING

| P1 | | P2 |
|--------|-------|----|
| 1(RI) | _____ | 8 |
| 2(CD) | _____ | 6 |
| 3(DTR) | _____ | 2 |
| 4(SG) | _____ | 5 |
| 5(RD) | _____ | 5 |
| 6(TD) | _____ | 3 |
| 7(CTS) | _____ | 4 |
| 8(RTS) | _____ | 7 |

| | | | | | |
|---|----------------|-----------|--|------|------|
| ⑩ | I.000001.0400R | TIE | TIE BLACK L=100MM | 1 | PCS |
| ⑨ | C.045P01.0100R | MOLDING | PVC 45P BLACK | 18.5 | G |
| ⑧ | C.000000.0000R | MOLDING | PE | 5.5 | G |
| ⑦ | J.000008.0500R | TIN WIRE | TIN WIRE OD:0.8MM | 1.5 | G |
| ⑥ | F.0081B0.0100R | TUBE | HEAT SHRINK TUBE COLOR:BLACK OD:1.0MM*L=8 | 8 | PCS |
| ⑤ | G.040245.3102R | SCREW | 4-40# SCREW COLOR BLACK | 4 | PCS |
| ④ | B.05008F.0G01R | CONNECTOR | RJ45 8P8C PLUG FEMALE SHELL NICKEL | 2 | PCS |
| ③ | B.02010M.0N00R | CONNECTOR | DB 9P/F PIN GOLD PLATED SHELL NICKEL PLASTIC BLUE | 1 | PCS |
| ② | B.02010M.0N00R | CONNECTOR | DB 9P/M PIN GOLD PLATED SHELL NICKEL PLASTIC BLUE | 1 | PCS |
| ① | A.030X01.0801R | CABLE | UL2835 CAT 5e UTP 26AWG(7/0.16TC)*4P JACKET PVC 60P BLACK OD:5.5±0.1mm L=1000mm | 2 | PCS |
| ⑩ | PAPT NO | ITFM | DFSCPIPTION | QTY | UNIT |

| | | | |
|---|---|----------|--------------------------------|
| DELOCK® we move the world | | | |
| Title: Seriell RS-232/422/485 Adapter DB9 | | | |
| Date | 2021 / 09 / 20 | Item no. | 63999 / 64122 |
| Unit | mm | Barcode | 4043619639991 4043619641222 |
| Projection |  | File No. | 88203 |
| Rev | A | | |