

Note:

1:All products must be 100% through the short circuit test.


2:Conditions:

1) DC:300V,1SEC.

2) Insulation Resistance:5MOHM.

Pin 1	black	Pin 4
Pin 2	red	Pin 3
Pin 3	white	Pin 2
Pin 4	yellow	Pin 1

wire list

						<div>This drawing is a controlled document for Iansan. It is subject to change and the controlling engineering organization should be contacted for the latest revision.</div> <div>Tolerance: 0&lt;, &lt;1.0 ±0.05 1.0&lt;&lt;4.0 ±0.10 4.0&lt;&lt;8.0 ±0.15 9.0&lt;&lt;15.0 ±0.30 15.0&lt;&lt;30.0 ±1.0</div> <div>View:</div> <div>Scale:FreeUnit:mm</div>
6						
5						
4						
3	HY 2.0 Tinned Copper, Terminal	Silvery White	8PCS			
2	HY 2.0 white shell	WHITE	2PCS			
1	UL 1007-24# black, red, white, yellow cord, L=500mm, HY 2.0 , Male	BL, R, W, Y	4PCS			

Date	2021 / 11 / 02	 Title: Universal IOT Grove Cable 4 x pin male to 4 x pin male 10 cm	
Unit	mm	Item no.	86953
Projection		Barcode	4043619869534
Rev	A	File No.	88251