


Dieser Pressprofileinsatz ist Zubehör für die Delock Crimpzangen 90528, 90527, 90295 und 90296. Die gummierten Handgriffe bieten dabei einen festen Halt während des Crimpvorganges. Der Pressprofileinsatz, die sog. Backen, sind auswechselbar, so dass für jeden Einsatz das passende Paar montiert werden kann.

90529
Hex crimp size: 9.14 mm (.360"), 8.23 mm (.324"), 6.65 mm (.262"), 1.73 mm (.068")
Coaxial cable suitable for crimping RG-59, RG-6
Material: 40Cr
Connectors suitable for crimping: e.g. F connectors



90530
Oval crimp size: 4.95 mm (.195"), 4.11 mm (.162"), 3.38 mm (.133"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-6
Material: 40Cr
Connectors suitable for crimping: Fiber optic SMA (oval)



90531
Hex crimp size: 8.23 mm (.324"), 4.52 mm (.178"), 1.73 mm (.068")
Coaxial cable suitable for crimping RG-58, RG-6, RG-174
Material: 40Cr
Connectors suitable for crimping: e.g. SMA, SMB




90532
Hex crimp size: 5.41 mm (.213"), 4.52 mm (.178"), 3.84 mm (.151"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-174, Belden 8281
Material: 40Cr
Connectors suitable for crimping: e.g. Fiber optic SMA, SMB



90533
Hex crimp size: 6.48 mm (.255"), 5.41 mm (.213"), 3.48 mm (.137"), 2.54 mm (.100"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-174
Material: 40Cr
Connectors suitable for crimping: Fiber optic e.g. LC, SC



90535
Hex crimp size: 5.41 mm (.213"), 3.84 mm (.151"), 3.25 mm (.128"), 2.54 mm (.100"), 1.75 mm (.069"), 1.09 mm (.043")
Coaxial cable suitable for crimping RG-58, RG-59, RG-174
Material: 40Cr
Connectors suitable for crimping: e.g. SMB, SMA, SMC, MCX



90536
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Material: 40Cr
Connectors suitable for crimping: e.g. Cable lugs, connection terminal, wire clamps, crimp connectors



90537
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Diameter: 1.25 - 5.5 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. flat receptacles, copper sleeve



90538
Cable suitable for crimping: AWG 14 - 22
Diameter: 0.5 - 2.5 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. Terminal crimp contacts for D-Sub



90539
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Diameter: 0.5 - 1.0 / 1.5 - 2.5 / 4.0 - 6.0 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. Cable lugs, connection terminal, wire clamps, crimp connectors



90528
Universal Coax Crimping Tool for 4 different diameters angled
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-6
Connectors suitable for crimping: e.g. SMA, SMB
Hex crimp size: 8.23 mm (.324"), 6.50 mm (.256"), 5.41 mm (.213"), 1.73 mm (.068")



90295
Universal Coax Crimping Tool for 6 different diameters
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-174, RG-140, RG-400
Connectors suitable for crimping: e.g. SMA, SMB
Hex crimp size: 6.48 mm (.255"), 5.41 mm (.213"), 3.50 mm (.137"), 2.54 mm (.100"), 1.73 mm (.068")

