

ELECTRICAL:


Current Rating: 1.5A Max.
Contact Resistance : 20m Ω MAX.
Insulation Resistance : 500M Ω MIN.
Dielectric Withstanding Voltage 1000V AC

MECHANICAL

Supporting Cable Diameter: 6~8.5mm
Operating Temperature: -10°C to +60°C
Storage Temperature: -40°C to +70°C

MATERIAL:

Housing: Zinc-alloy ,Nickel Plated
Contact:Phosphor bronze, 50u" Gold Plating
Press Cover : PC

| | |
|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <p>Line: D-Type R445 built-in connector with LSA connection Cat.6A STP metal</p> | |
| <p>Date</p> | <p>2024 / 05 / 31</p> |
| <p>Unit</p> | <p>mm</p> |
| <p>Projection</p> | <p></p> |
| <p>Rev</p> | <p>A</p> |
| <p>Item no.</p> | <p>67064</p> |
| <p>Barcode</p> | <p>4043619670642</p> |
| <p>File No.</p> | <p>88467</p> |



we move the world

Title: D-Type RJ45 built-in connector with
LSA connection Cat.6A STP metal

| | |
|----------|-------|
| Item no. | 67064 |
|----------|-------|

| | |
|---------|---------------|
| Barcode | 4043619670642 |
|---------|---------------|

| | |
|----------|-------|
| File No. | 88467 |
|----------|-------|