

Delock Wall Socket with 2 x USB Type-A Charging Port 2.4 A

Description

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB Type-A charging ports. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.



Item no. 11471

EAN: 4043619114719

Country of origin: China

Package: Box

Technical details

- Connectors:
 - 1 x power socket CEE 7/3 with childproof lock
 - 2 x USB Type-A charging port max. 2.4 A
 - 3 x screw terminal for PE, N, L
- Robust plastic housing
- Rated current: 16 A / 250 V~
- Rated power: 4000 W
- USB Charger:
 - Input: AC 250 V / 50 Hz / 0.2 A
 - USB output: max. 5 V / 2.4 A total
 - Short circuit protection
- Suitable for standard installation box
- Dimensions (LxWxH): ca. 80 x 80 x 53 mm
- Colour: white

System requirements

- Mains supply with grounding
- A free standard installation box

Package content

- Power socket
- User manual

Images



General

| | |
|----------------|--|
| Mounting type: | in-wall |
| Protection: | Input overvoltage protection Short circuit protection |

Interface

| | |
|--------------|---|
| Connector 1: | 1 x 3 pin terminal block screw terminal |
| Connector 2: | 1 x Steckdose CEE 7/3 mit Kindersicherung |
| connector 3: | 2 x USB Type-A female |

Physical characteristics

| | |
|---------|---------|
| Length: | 80 mm |
| Width: | 80.0 mm |
| Height: | 56 mm |
| Colour: | white |