

Delock Multi Socket Cube 3-way with childproof lock and USB PD 3.0 charger 20 W white

Description

The extension socket by Delock with USB charging function is suitable for extending sockets on an existing socket outlet.

Make 3 out of 1

Whether in the kitchen, living area or office. There is a lack of free sockets. This multiple socket makes three out of one free grounded socket. The cube shape also provides a space-saving solution.

USB charger included

In addition to the sockets, one USB Type-C™ and one USB Type-A charging ports are provided. Common fast charging technologies, such as Power Delivery (PD) 3.0, are supported. This makes the charging process as safe and fast as possible.



Item no. 11501

EAN: 4043619115013

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x plug CEE 7/7
 - Output:
 - 3 x power socket CEE 7/3 with childproof lock
 - 1 x USB Type-A female
 - 1 x USB Type-C™ female
- Rated current: 16.0 A / 250 V~
- Rated power: 3680.0 W
- LEDs for status monitoring
- USB Charger:
 - Input: AC 250 V / 50 Hz / 0.5 A
 - Output power: max. 20.0 W total
 - USB-A: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A
 - USB-C™: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A
 - Over current protection, over heating protection, short circuit protection
- Average active efficiency 82.06 %

- Efficiency at low load (10 %) 78.21 %
- No-load power consumption 0.138 W
- Colour: white
- Dimensions (LxWxH): ca. 66 x 66 x 87 mm

Package content

- Extension socket
- User manual

Images



General

| | |
|-------------|--|
| Protection: | Input overvoltage protection Short circuit protection Overheating protection |
|-------------|--|

Interface

| | |
|--------------|--|
| Connector 1: | 1 x plug CEE 7/7 |
| Connector 2: | 3 x Steckdose CEE 7/3 mit Kindersicherung |
| connector 3: | 1 x USB Type-C™ Power Delivery female 1 x USB Type-A female |

Physical characteristics

| | |
|---------|-------|
| Length: | 66 mm |
| Width: | 66 mm |
| Height: | 87 mm |
| Colour: | white |

Power supply

| | |
|---------|--|
| Input: | AC 100 - 240 V / 50 - 60 Hz / 0.5 A |
| Output: | 5.0 V / 3.0 A 12,0 V / 1,67 A 9,0 V / 2,22 A |