

Delock Antena LTE / GSM / UMTS macho SMA 3 dBi omnidireccional fija con base magnética y cable de conexión RG-174 2 m para exteriores negro

Descripción

Esta antena de Delock permite utilizar diferentes bandas LTE, GSM y UMTS dentro y fuera. Es completamente compatible con Bluetooth, WLAN 2,4 GHz, ZigBee, DECT, Z-Wave y LoRa 868 MHz / 915 MHz.



Número de elemento 12416

EAN: 4043619124169

Pais de origen: Taiwan,
Republic of China

Paquete: Poly bag

Detalles técnicos

- Conector: 1 x macho SMA
- Intervalo de frecuencias:
800 - 960 MHz
1710 - 2700 MHz
- GSM, UMTS, Bluetooth, WLAN 2,4 GHz, ZigBee, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Ganancia de la antena: 3 dBi
- Impedancia: 50 ohmios
- Polarización: vertical
- VSWR: 2,0
- Temperatura de funcionamiento: -30 °C ~ 70 °C
- Color: negro
- La longitud de la antena incluida la base magnética: 88,7 mm aproximadamente
- Cable: coaxial
- Tipo de cable: RG-174
- Color del cable: negro

- Pérdida del cable: 1,5 dB @ 1,5 GHz por metro
 - Diámetro del cable: aprox. 2,7 mm
 - Longitud del cable conector incluido: aprox. 2 m
 - Diámetro de la base magnética: 29,0 mm aproximadamente
-



Requisitos del sistema

- Dispositivo con un conector SMA disponible
-


Contenido del paquete

- Antena


Image




Far-field amplitude 100000 - E azi
 Frequency: 100000 Hz
 Power: 100000 mW
 Gain: 100000 dBi
 Directivity: 100000 dBd
 Efficiency: 100000 %
 ...




Far-field amplitude 170000 - E azi
 Frequency: 170000 Hz
 Power: 170000 mW
 Gain: 170000 dBi
 Directivity: 170000 dBd
 Efficiency: 170000 %
 ...




Far-field amplitude 200000 - E azi
 Frequency: 200000 Hz
 Power: 200000 mW
 Gain: 200000 dBi
 Directivity: 200000 dBd
 Efficiency: 200000 %
 ...




Far-field amplitude 270000 - E azi
 Frequency: 270000 Hz
 Power: 270000 mW
 Gain: 270000 dBi
 Directivity: 270000 dBd
 Efficiency: 270000 %
 ...




Far-field amplitude 300000 - E azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - E azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - E azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - E azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - E azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...




Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...



Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...



Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...



Far-field amplitude 300000 - H azi
 Frequency: 300000 Hz
 Power: 300000 mW
 Gain: 300000 dBi
 Directivity: 300000 dBd
 Efficiency: 300000 %
 ...

General

Mounting type:	magnetic
Suitable for indoor:	Si
Suitable for outdoor:	Si

Interface

conector :	1 x macho SMA
------------	---------------

Technical characteristics

Frequency range:	1710 - 2700 MHz 800 - 960 MHz
Antenna gain:	3 dBi
Gain:	0 - 3 dBi
Impedanciaios:	50 Ω
Temperatura de funcionamiento:	-30 °C ~ 70 °C
Polarisation:	vertikal
VSWR:	2,0

Physical characteristics

Antenna type:	omnidireccional
Antenna length incl. magnetic base:	88,7 mm
Diameter magnetical base:	29 mm
Height magnetical base:	18.7 mm
Cable category:	coaxial
Cable type:	RG-174
Cable attenuation:	1.5 dB @ 1.5 GHz per meter
Color del cable:	negro

Cable length incl. connector:	2 m
Acabado del conector:	chapado en oro
Color:	negro