

Delock Ergonomic USB Mouse vertical - RGB Illumination

Description

This wired vertical USB mouse by Delock is suitable for right handers and can be connected to a free USB port of a PC or laptop. Due to its ergonomic design, the hand remains in upright position and does not have to be turned. Thus the mouse can be used preventive or with starting pain e.g. RSI (Repetitive-Strain-Injury). There are four adjustable DPI levels to adapt the sensitivity of the mouse.

RGB Touch function

The mouse stands out due to its RGB touch function. By touching the fingerprint symbol on the topside of the mouse, there are four different colour modes which can be set. The upper edge will illuminate in the desired colour.



Item no. 12597

EAN: 4043619125975

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-A male
- For right handers
- 4 standard buttons, 1 scroll wheel and 1 DPI button
- Touch function for setting the RGB illumination
- 4 different colour settings:
 1. Touch: fast colour gradient
 2. Touch: 8 colours light up consecutively
 3. Touch: 8 colours light up selectively
 4. Touch: smooth colour gradient
 5. Touch: RGB illumination switches off
- Polling rate: 125 Hz
- Sensitivity: 1000 / 1200 / 1600 / 2500 dpi
- Operating temperature: 0 °C ~ 40 °C
- Plug & Play
- Dimensions (LxWxH): ca. 113 x 79 x 80 mm
- Cable length: ca. 1.5 m
- Weight: ca. 132 g
- Colour: black

System requirements

- Linux Kernel 2.6 or above
- Windows Vista/7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- Mouse
- User manual

Images



General

Function:	Plug & Play
Style:	Right handers

Interface

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

Technical characteristics

Operating temperature:	0 °C ~ 40 °C
Sensibility:	1000 / 1200 / 1600 / 2500 dpi

Physical characteristics

Weight:	132 g
Cable length:	1.5 m
Length:	113 mm
Width:	79.0 mm
Height:	80 mm
Colour:	black
Buttons:	4 standard buttons, 1 scroll wheel and 1 DPI button