

# Delock Antenna Cable N plug > RP-SMA plug CFD400 LLC400 5 m low loss

## Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a very low attenuation.



5 m

**Item no. 13023**

EAN: 4043619130238

Country of origin: Taiwan,  
Republic of China

Package: Box

## Technical details

- Connector: N plug > RP-SMA plug
- Cable type: CFD400, LLC400
- Impedance: 50 Ohm
- Cable Attenuation:
  - 2.4 GHz: ca. 0.22 dB per meter
  - 5.7 GHz: ca. 0.35 dB per meter
- Diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Colour: black
- Cable length: ca. 5 m


## System requirements

- Device with a free RP-SMA connector

## Package content

- Antenna cable

## Images



### Interface

Connector 1:	N plug
Connector 2:	RP-SMA plug

### Technical characteristics

Impedance:	50 Ω
------------	------

### Physical characteristics

Cable type:	CFD400, LLC400
Cable attenuation:	2.4 GHz: ca. 0.22 dB per meter 5.7 GHz: ca. 0.35 dB per meter
Cable colour:	black
Cable length:	5 m
Smallest bending radius:	51.5 mm