

# Delock HDMI Splitter 1 x HDMI in to 2 x HDMI out 4K 60 Hz with downscaler

## Description

This splitter by Delock receives an HDMI signal from a PC or laptop and splits it to two connected displays. Thereby **one HDMI connection** can be used to operate **two HDMI monitors**.

## Downscaler

If a monitor does not support the high resolution, the image can be scaled from 4K to 1080p with the integrated downscaler.

## USB powered

The device is powered via a USB port, a suitable USB cable is included. If no free USB-A port is available, an optional external power supply is required.



**Item no. 18651**

EAN: 4043619186518

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - Input:
    - 1 x HDMI-A female
    - 1 x USB Type Micro-B female (5 V power supply)
  - Output:
    - 2 x HDMI-A female
- Supports EDID management
- High Speed HDMI specification
- Supports 3D displays
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Function: Mirrored
- Transmission of audio and video signals
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Video bandwidth up to 600 MHz / 6 Gbps per channel, max. 18 Gbps
- Power consumption: max. 2.5 W
- Robust metal housing

- Colour: black
- Dimensions (LxWxH): ca. 90 x 44 x 14 mm

---

## System requirements

- HDMI cable
- Power source with a free USB Type-A female port

---

## Package content

- HDMI Splitter
- USB power cable, length: ca. 0.75 m
- User manual

---

## Images



## General

Specification:	High Speed HDMI HDCP 1.4 HDCP 2.2
----------------	-----------------------------------------

## Interface

Output:	2 x HDMI-A female
Input:	1 x USB Type Micro-B female (5 V power supply) 1 x HDMI female

## Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps

## Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	90 mm
Width:	44 mm
Height:	14 mm