

Delock Riser Card PCI Express x1 > x16 with 60 cm **USB** cable

Description

The PCI Express riser card by Delock can be plugged into any PCI Express x1 slot on the motherboard. Then the x16 PCI Express slot can be mounted in a different position in the case. This allows a graphics card to be operated in each PCIe slot of a motherboard, even if the graphics card is wider than a single slot. By using several riser cards, several graphics cards can be operated simultaneously on one motherboard, e.g. for mining crypto currencies such as Bitcoin, Ethereum or Zcash.

Note


The package content includes a USB 3.0 riser cable with a length of 60 cm. No USB signals are transmitted through this cable, therefore it is not possible to exchange it with a different or longer cable.

Special features

A PCIe x16 graphics card can be used with a PCIe x1 slot.

Technical details

- Connectors: Motherboard side: 1 x PCI Express x1 1 x USB 3.0 Type-A female Riser side: 1 x PCI Express x16
 - 1 x USB 3.0 Type-A female
 - 1 x 6 pin PCIe power female
- Data transfer rate up to 800 MB/s
- 4 x FP solid capacitors, ensures secure power supply of the graphics card
- 4 x mounting holes on the riser card
- Bottom side with isolating, antislip pad



www.delock.com

41426

Item no. 41426

EAN: 4043619414260 Country of origin: China Package: Retail Box

1/3

DATASHEET



- Cable data:
 - 1 x riser cable USB 3.0 Type-A male to male ca. 60 cm (incl. connectors)
- 1 x power cable 6 pin to SATA ca. 20 cm (incl. connectors)
- Dimensions of the riser card (LxWxH): ca. 128.25 x 43.50 x 21.20 mm
- OS independent, no driver installation necessary

System requirements

- PC with one free PCI Express x1 / x4 / x8 / x16 / x32 slot
- Power supply with a free SATA power connector

Package content

- PCIe to USB riser card
- USB to PCIe riser card
- USB 3.0 cable
- Power cable

Images



DATASHEET



General

Supported operating system. OS independent, no driver installation necessary	Supported operating system:	OS independent, no driver installation necessary
--	-----------------------------	--

Technical characteristics

Physical characteristics

Length:	128.25 mm
Width:	43.50 mm
Height:	21.20 mm