

Delock External Enclosure 2 x M.2 Key B > SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) with RAID

Description

The aluminium enclosure by Delock enables the installation of two M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop. When using more than one SSD, there is the possibility to use different RAID level.



<u>M.2</u>

Item no. 42588

EAN: 4043619425884 Country of origin: Taiwan, Republic of China Package: Retail Box

Technical details

- Connector: external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type Micro-B female internal: 2 x 67 pin M.2 key B slot
- Interface: SATA
- Chipset: Asmedia ASM1352R
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B based on SATA
- Maximum height of the components on the module: 1.25 mm application of double-sided assembled modules supported
- Supports RAID 0, 1, SPAN, Port Multiplier
- Switch for RAID mode
- Reset button
- Data transfer rate up to 6 Gb/s
- 2 x LED indicator for power and access
- Operating temperature: 0 °C ~ 70 °C
- Storage temperature: -20 °C ~ 70 °C
- Dimensions (LxWxH): ca. 100 x 80 x 17 mm
- Hot Plug, Plug & Play

DATASHEET



System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

Package content

- External enclosure
- Screwdriver, screws
- Cable USB 3.1 Type-A to Type Micro-B, length ca. 40 cm
- User manual

Images



DATASHEET



General

Function:	Hot Plug Plug & Play
Internal construction:	full PCB
Supported operating system:	Linux Kernel 3.19 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x USB 10 Gbps Type Micro-B female
Internal:	2 x 67 pin M.2 key B slot

Technical characteristics

Chipset:	Asmedia ASM1352R
Data transfer rate:	USB 10 Gbps up to 10 Gb/s
RAID function:	SPAN 0 1 Port Multiplier

Physical characteristics

Housing material:	Aluminium
Length:	100 mm

DATASHEET



Width:	80 mm
Height:	17 mm
Colour:	black