

# Delock External Enclosure for 2.5" SATA HDD / SSD with additional USB Type-C™ and Type-A Port and SD Slot

## Description

The aluminium enclosure by Delock enables the installation of a **2.5" SATA HDD / SSD**. Different USB devices can be connected to the **USB Type-A and USB Type-C™** port. The **SD** slot could be used for reading and writing SD memory cards. The enclosure can be connected via USB cable to the PC or laptop.

### Sturdy housing with cooling fins

The sturdy metal housing has holes below the 2.5" installation slot, which are located directly above the cooling fins when installed in the outer frame. This ensures **optimum cooling** of the enclosure and the built-in memory.

### Additional power socket

The USB-C™ power socket is used for power supply to the devices and memory which are connected to the enclosure. The enclosure can also be operated without an additional power supply.



**Item no. 42618**

EAN: 4043619426188

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external:
    - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female >
    - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
    - 1 x USB 3.0 Type-A female
    - 1 x SD slot
    - 1 x USB Type-C™ female (power supply 5 V)
  - internal:
    - 1 x SATA 6 Gb/s 22 pin receptacle
- Chipset: JMicron JMS578, Genesys Logic GL3523, GL3224
- Data transfer rate up to 5 Gb/s
- Suitable for 2.5" SATA HDD / SSD:
  - HDD height up to 9.5 mm

SATA HDD / SSD up to 6 Gb/s

- 5 x LED indicator
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 112 x 112 x 22 mm
- Hot Plug, Plug & Play

---

## System requirements

- Android 8.0 or above
- Chrome OS 72.0 or above
- Linux Kernel 3.18 or above
- Mac OS 10.14.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A or USB Type-C™ port

---

## Package content

- External enclosure
- Cable USB-C™ male to USB Type-A male, length ca. 40 cm
- Cable USB-C™ male to USB-C™ male, length ca. 40 cm
- Screws
- Screwdriver
- 4 x rubber pad
- User manual

---

## Images



## General

Suitable for data medium:	2.5"
Supported operating system:	Android 8.0 or above Chrome OS 72.0 or above Linux Kernel 3.18 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

External:	1 x SD slot 2 x USB 5 Gbps USB Type-C™ female 1 x USB Type-C™ female (power supply) 1 x USB 5 Gbps Type-A female
Internal:	1 x SATA 6 Gb/s 22 pin receptacle

## Technical characteristics

Chipset:	Genesys Logic GL3523 Genesys Logic GL3224 JMicron JMS578
----------	--

## Physical characteristics

Housing material:	Aluminium
Length:	112 mm
Width:	112 mm
Height:	22 mm
Colour:	black