

Delock External Enclosure for 3.5" SATA HDD with USB Type-C™ female transparent - tool free

Description

This plastic enclosure by Delock can be used for the installation of a **3.5" SATA hard drive**. The included USB cables allow the connection to a free USB Type-A or USB-C™ port.

Transparent enclosure with stand

The **sturdy, transparent plastic housing** provides a view inside to quickly see which memory is inside. A stand is supplied for vertical operation.

HDD installation without tools

The special feature of this enclosure is that **no tools** are required to install the HDD. The lid can be pushed backwards by a little pressure, the HDD will be attached to the SATA port and then the lid is reattached until it locks.



Item no. 42623

EAN: 4043619426232

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - external:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
 - 1 x DC jack
 - internal:
 - 1 x SATA 6 Gb/s 22 pin receptacle
- On / Off switch
- Suitable for 3.5" SATA HDD:
 - SATA HDD up to 6 Gb/s
 - HDD up to 10 TB
- Chipset: VIA VL716
- Data transfer rate:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- LED indicator for power and access

- Transparent plastic housing
 - Dimensions (LxWxH): ca. 179 x 116 x 30 mm
 - Hot Swap, Plug & Play
-

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1 A
 - Output: 12 V / 2 A
 - Ground outside, plus inside
 - Dimensions:
 - inside: \varnothing ca. 2.0 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 10 mm
-

System requirements

- Chrome OS 75.0 or above
 - Linux Kernel 3.3 or above
 - Mac OS 10.14.6 or above
 - Windows 7/7-64/8.1/8.1-64/10/10-64
 - PC or laptop with a free USB Type-C™ port or
 - PC or laptop with a free USB Type-A port
-

Package content

- 3.5" external enclosure
- Cable USB-C™ male to USB-C™ male, length ca. 50 cm
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Stand
- Power supply
- User manual

Images



General

| | |
|-----------------------------|---|
| Function: | Hot Swap Plug & Play |
| Suitable for data medium: | 2.5" 3.5" SSD or HDD |
| Supported operating system: | Chrome OS 75.0 or above Linux Kernel 3.3 or above Mac OS 10.14.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |

Interface

| | |
|-----------|--|
| External: | 1 x DC jack 1 x USB 5 Gbps USB Type-C™ female |
| Internal: | 1 x SATA 6 Gb/s 22 pin receptacle |

Technical characteristics

| | |
|----------|-----------|
| Chipset: | VIA VL716 |
|----------|-----------|

Physical characteristics

| | |
|-------------------|-------------|
| Housing material: | Plastic |
| Length: | 179 mm |
| Width: | 116 mm |
| Height: | 30 mm |
| Colour: | transparent |