

Delock External Enclosure for M.2 NVMe PCIe SSD with SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C[™] female

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260, 2242 and 2230 format, it can be connected via USB to the PC or laptop. The robust metal housing ensures an optimum temperature of the memory.

Note

There is no support for SATA M.2 SSD.



Item no. 42634

EAN: 4043619426348 Country of origin: China Package: Retail Box

Technical details

• Connectors:

external: 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C[™] female internal: 1 x 67 pin M.2 key M slot

- Chipset: Realtek RTL9210
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of doublesided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing
- Dimensions (LxWxH): ca. 104 x 28 x 11 mm
- Hot Plug, Plug & Play

System requirements

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.





- Linux Kernel 3.3 or above
- Mac OS 10.15.2 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C[™] port

Package content

- External enclosure M.2
- Mounting material
- Cable USB-C[™] male to USB-C[™] male, length ca. 30 cm
- Cable USB-C[™] male to USB Type-A male, length ca. 30 cm
- 1 x thermal pad
- User manual

Images



DATASHEET



General

Function:	NVM Express (NVMe) Hot Plug Plug & Play
Internal construction:	full PCB
Supported operating system:	Linux Kernel 3.3 or above Mac OS 10.15.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe $% \left({{\left({{{\rm{A}}} \right)}_{{\rm{A}}}} \right)$
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key M slot

Technical characteristics

Chipset:	Realtek RTL9210
Data transfer rate:	up to 10 Gbps

Physical characteristics

Housing material:	Aluminium
Cable length:	30 cm
Length:	104 mm
Width:	28 mm
Height:	11 m
Colour:	silver