

# Delock M.2 SSD PCIe / NVMe Key M 2280 - 1 TB

## Description

This flash module by Delock is a memory in the M.2 format for the PCIe / NVMe interface. With its 80 mm length, it has the form factor 2280. The module supports PCIe x4 and has the revision 3.0. The high read and write speed supports fast data transfer even for big amount of data, which is particularly important in the photo and video range.



1 TB

**Item no. 54081**

EAN: 4043619540815

Country of origin: China

Package: Antistatic cover

## Technical details

- Connector:  
1 x 67 pin M.2 Key M male
- Capacity: 1 TB
- Interface: PCIe x4 Rev. 3.0
- Controller: SMI SM2263XT
- Maximum read speed: 2000 MB/s
- Maximum write speed: 1700 MB/s
- Power consumption: max. 2 W
- MTBF: 1.000.000 hours
- Flash type: TLC
- Maximum write cycles: 1000
- Storage temperature: -55 °C ~ 115 °C
- Operating temperature: 0 °C ~ 70 °C
- Shock: 1500G
- Operating vibration: 16G
- Humidity: 5 ~ 98 %
- Supports TRIM
- Supports S.M.A.R.T.
- Supports NVM Express (NVMe) 1.3
- Dimensions (LxWxH): ca. 80.0 x 22.0 x 2.1 mm

---

## System requirements

- A free M.2 key M slot based on PCIe

---

## Package content

- M.2 SSD

---

## Images



## Interface

connector:	1 x 67 pin M.2 Key M male
------------	---------------------------

## Technical characteristics

Storage temperature:	-55 °C ~ 115 °C
Read:	2000 MB/s
Maximum power consumption:	2 W
Maximum write cycles:	1000
MTBF:	1.000.000 hours
Interface:	PCIe x4 Rev. 3.0
Shock:	1500 G
Write:	1700 MB/s
Capacity:	1 TB
Vibration:	16 G
Flash type:	TLC

## Physical characteristics

Length:	80.0 mm
Width:	22.0 mm
Height:	2.1 mm