

Delock SATA 6 Gb/s Flash Module 4 GB MLC Low profile

Description

- SATA 6Gb/s interface
- iSmart disk health monitoring
- Intelligent error recovery syteme
- Excellent data transfer speed
- Zero mechanical design
- Anti vibration mechanical design



4 GB

Item no. 54653

EAN: 4043619546534

Country of origin: Taiwan,
Republic Of China

Package: Antistatic cover

Technical details

- Capacity 4 GB
- Interface SATA 6 Gb/s
- Pin 7 Power
- Chip Toshiba A19
- Typ MLC
- Max. Channel 1
- Maximum data transmission depending on the storage capacity and system configuration: max. 300 MB / sec read / 80 MB / sec writing
- Power consumption: max. 0.6 W (5V x 125 mA)
- Operating temperature: 0° C bis +70° C;
- Storage temperature: -55° C bis +95° C
- Supports ATA Security und S.M.A.R.T.
- MTBF: >3.000.000 hours
- Maximum write cycles: 3000
- Vibration: 20G, 7 - 2000 Hz
- Shock: 1500G, 0.5 ms
- Dimension: 32.5 x 29.5 x 8.0 mm
- low profile

System requirements

- One free SATA 6 Gb/s 7 pin slot

Package content

- SATA Dom