

Delock SATA 6 Gb/s Flash Module 64 GB MLC Low profile

Description

- SATA 6Gb/s interface
- iSmart disk health monitoring
- Intelligent error recovery syteme
- Excellent data transfer speed
- Zero mechanical design
- Anti vibration mechanical design
- Write protection



64 GB

Item no. 54660

EAN: 4043619546602

Country of origin: Taiwan,
Republic Of China

Package: Antistatic cover

Technical details

- Capacity 64 GB
- Interface SATA 6 Gb/s
- Pin 7 Power
- Chip Toshiba
- Typ MLC
- Max. Channel: 2
- Maximum data transmission depending on the storage capacity and system configuration: max. 290 MB / sec read / 80 MB / sec writing
- Power consumption: max. 2A (5V x 400mA)
- Operating temperature: 0° C bis +70° C;
- Storage temperature: -55° C bis +95° C
- Supports Write Protect, ATA Security and S.M.A.R.T.
- MTBF: >3.000.000 Std.
- Maximum write cycles: 3000
- Vibration: 20G, 7 - 2000 Hz
- Shock: 1500G, 0.5 ms
- Dimension: 32.5 x 29.5 x 8.0 mm
- low profile

System requirements

- One free SATA 6 Gb/s 7 pin slot

Package content

- SATA Dom