

# Delock Adapter USB 2.0 Type-A to 1 x Serial RS-232 D-Sub 9 + Adapter D-Sub 25

## Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.



1,8 m

**Item no. 61314**

EAN: 4043619613144

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - Cable:
    - 1 x USB 2.0 Type-A male >
    - 1 x serial RS-232 DB9 male with screws
  - Adapter:
    - 1 x serial RS-232 DB9 female >
    - 1 x serial RS-232 DB25 male
- Chipset: FTDI FT232RL
- Compatible with USB 3.0, USB 2.0, and USB 1.1
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Data transfer rate up to 460.8 Kbps
- Cable length: ca. 1.8 m
- Colour: black / transparent

## System requirements

- Linux Kernel 5.8.0 or above

- Mac OS 11.4 or above
- Windows 8.1/8.1-64/10/10-64/11
- Windows Server 2016/Windows Server 2019
- PC or laptop with a free USB Type-A port


---

## Package content

- USB 2.0 to 1 x serial adapter
- Adapter DB9 to DB25
- Driver CD
- User manual

---

## Images



## General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2008 R2 Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11

## Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 male

## Technical characteristics

Chipset:	FTDI FT232RL
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Current consumption:	20 mA
UART:	USB to serial UART

### Physical characteristics

Cable colour:	transparent
Cable length incl. connector:	1.8 m
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double
Colour:	black