

Adapter USB 2.0 Type-A > 1 x Serial DB9 RS-232

Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.



1 m

Item no. 61364

EAN: 4043619613649

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- Connectors:
1 x USB 2.0 Type-A male >
1 x serial RS-232 DB9 male with nuts
- Chipset: FTDI
- Data transfer rate up to 1 Mb/s
- Cable length: ca. 1 m


System requirements

- Windows Server-2003/Server-2008/Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

Images



General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	3 x PWR / RXD / TXD

Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 male

Technical characteristics

Chipset:	FTDI 232BL
Data transfer rate:	up to 921.6 Kbps
FIFO:	384 Byte RX 128 Byte TX
Operating temperature:	0 °C ~ 60 °C
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Current consumption:	max. 40 mA

Physical characteristics

Housing colour:	transparent
-----------------	-------------

Cable colour:	transparent
Cable length incl. connector:	1.1 m
Screw type:	#4-40 UNC
Shielding:	double
Colour:	black