

Delock Adapter USB 2.0 > 1 x Serial RS-422/485

Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.



Item no. 62406

EAN: 4043619624065

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
Adapter:
1 x USB 2.0 Type-A male >
1 x serial RS-422/485 D-Sub 9 pin male
Terminal block:
1 x serial RS-422/485 D-Sub 9 pin female >
1 x 6 pin terminal block
- Chipset: FTDI
- Serial connector with nuts
- Data transfer rate up to 230.4 Kbps
- Cable length incl. connectors: ca. 0.8 m

System requirements

- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial RS-422/485 adapter
- Terminal block adapter
- Driver CD
- User manual

Images



G2406	DB9 Buchse/Female		TerminalBlock/Terminal Block
	RS-422	RS-485	RS-422/RS-485
1	Transmit (A-) / T/R (A-)	T/R (A-)	T/R (A-)
2	Transmit (B+) / T/R (B+)	T/R (B+)	T/R (B+)
3	Receive (A-) / NC	NC	Receive (A-)
4	Receive (B+) / NC	NC	Receive (B+)
5	Signal GND (SG)	Signal GND (SG)	Signal GND (SG)
6	NC	NC	NC
7	NC	NC	NC
8	NC	NC	NC
9	NC	NC	NC

General

Function:	Plug & Play
Specification:	RS-422 / RS-485 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.14.1 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11
Protection:	ESD (Electrostatic Discharge)

Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-422/485 DB9 male
connector 3:	1 x 6 Pin Terminal Block

Technical characteristics

Chipset:	FTDI 232R
Data transfer rate:	bis zu 230,4 Kbps
Data transmission:	asynchronous Half duplex full duplex differential
UART:	USB to serial UART
Resistor:	Termination resistors 120 Ω
Support:	Modbus

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Cable colour:	brown transparent
Cable length incl. connector:	0.8 m
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double