

Delock Audio Converter Analogue > Digital

Description

The audio converter by Delock converts an analogue stereo signal into a digital signal. Two cinch cables can be connected to the device to input the analog source signal, e. g. from an MP3 player. At the output, the signal can be transmitted either via optical TOSLINK connection or via S/PDIF coaxial connection.



Item no. 62443

EAN: 4043619624430

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 2 x RCA female
 - 1 x DC jack
 - Output:
 - 1 x TOSLINK female S/PDIF
 - 1 x Coaxial female S/PDIF
- Sample rate: 16 Bit / 48 kHz
- Robust metal housing
- Dimensions (LxWxH): ca. 63 x 41 x 21 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm

outside: \varnothing ca. 5.5 mm

length: ca. 9 mm

System requirements

- Analogue audio signal
- Connection cable

Package content

- Converter analogue > digital
- Power supply
- User manual

Images



Interface

Output:	1 x Coaxial female S/PDIF 1 x TOSLINK female S/PDIF
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 2 x RCA female (red, white)

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Length:	63 mm
Width:	41 mm
Height:	21 mm