

Delock Adapter USB 2.0 Type-A to 1 x Serial RS-232 D-Sub 9 pin male with nuts 1.5m

Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.



1,5 m

Item no. 62645

EAN: 4043619626458

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x serial DB9 male with nuts
- Chipset: Prolific PL-2303 GS
- Data transfer rate up to 460.8 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 1.5, 2
- Databits: 5, 6, 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- Cable length incl. connectors: ca. 1.5 m

System requirements

- Linux Kernel 5.11 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

Images



General

| | |
|----------------|-------------------------------|
| Function: | Plug & Play |
| Specification: | RS-232 (EIA / TIA) USB 2.0 |

Interface

| | |
|--------------|-----------------------------------|
| Connector 1: | 1 x USB 2.0 Type-A male |
| Connector 2: | 1 x serial Sub-D 9 male with nuts |

Technical characteristics

| | |
|----------------------|--|
| Chipset: | Prolific PL2303GS |
| Data transfer rate: | up to 460,8 Kbps |
| FIFO: | 1 x 1024 Byte |
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |
| Data transmission: | asynchronous full duplex |
| UART: | USB to serial UART |
| Data bits: | 5, 6, 7, 8 |

Physical characteristics

| | |
|-------------------------------|----------------------|
| Cable length incl. connector: | 1.5 m |
| Pin finishing: | gold-plated |
| Screw type: | #4-40 UNC |
| Shielding: | double |
| Colour: | transparent black |