


Delock 2.5" Converter USB 10 Gbps Micro-B female to M.2 / mSATA with enclosure

Description

This Delock converter enables the connection of an M.2 SSD in 2280, 2260, 2242 and 2230 format or an mSATA SSD in half size or full size format. If both slots are occupied, only the M.2 SSD can be used. The converter can be installed into the system through the USB interface.



Item no. 62731

EAN: 4043619627318 Country of origin: Taiwan, Republic of China Package: Box

Technical details

- Connectors:
 - 1 x USB 10 Gbps Type Micro-B female
 - 1 x 67 pin M.2 key B slot
- 1 x mSATA slot (half size / full size)
- Interface: SATA
- Form factor: 2.5"
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.35 mm, application of double-sided assembled modules supported
- LED indicator
- Maximum current for M.2 module: 3 A
- Short circuit protection, over heating protection
- ESD protection up to 2 kV
- Dimensions (LxWxH): ca. 100 x 70 x 9 mm

System requirements

DATASHEET



- Linux Kernel 4.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- A free USB interface

Package content

- Converter
- 2.5" enclosure
- Fixing screws for M.2 module, mSATA module and enclosure
- USB cable, length ca. 35 cm
- Cooling pad for M.2 and mSATA module
- User manual

Images





General

Form factor:	2.5"
Slot:	SATA
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
Maximum height of the components on the module:	1.35 mm application of double-sided assembled modules supported

Interface

Connector 1:	1 x USB 10 Gbps Type Micro-B female
Connector 2:	1 x 67 pin M.2 key B slot
connector 3:	1 x mSATA slot (half size / full size)

Physical characteristics

Length:	100 mm
Width:	70 mm
Height:	9 mm