

Delock Adaptor USB Type-C™ la 1 x serial RS-232 D-Sub 9 pini tată cu șuruburi 0,25 m

Descriere scurta

Acest adaptor USB Type-C™ la serial de la Delock oferă o interfață compatibilă RS-232 DB9 pentru imprimante, instrumente de măsură, controale, dispozitive IoT etc.



0.25 m

Nr. 64125

EAN: 4043619641253

Țara de origine: China

Pachet: Retail Box

Detalii tehnice

- Conectori:
 - 1 x USB Type-C™ tată
 - 1 x seriale DB9 tată, cu șuruburi
- Chipset: FTDI FT232RL
- Rată de transfer a datelor de până la 230,4 Kbps
- Semnale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Lungime cablu, inclusiv conectori: cca. 0,25 m
- Culoare: negru

Cerinte de sistem

- Linux Kernel 2.6 sau superior
- Mac OS 10.13 sau superior
- Windows 8.1/8.1-64/10/10-64/11
- PC sau laptop cu un port USB Type-C™ sau Thunderbolt™ 3 liber

Pachetul contine

- USB Type-C™ la 1 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Imagini



General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) Thunderbolt™ 3 USB Type-C™
Supported operating system:	Linux Kernel 2.6 sau superior Mac OS 10.13 sau superior Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

Output:	1 x RS-232 seriale DB9, tată
Input:	1 x USB Type-C™ tată

Technical characteristics

Chipset:	FTDI FT232RL
Data transfer rate:	up to 460,8 Kbps
FIFO:	1 x 256 byte receiver 1 x 128 byte transmit
Data transmission:	asynchronous full duplex
UART:	USB to serial UART

Physical characteristics

Cable length incl. connector:	25 cm
Pin finishing:	placat cu aur
Conductor gauge:	28 AWG data line 24 AWG power line
Tipul șurubului:	#4-40 UNC

Shielding:	double
Colour:	negru