

Delock USB Type-C™ Converter for 1 x M.2 NVMe SSD + 1 x SATA SSD / HDD with Clone Function

Description

This converter by Delock enables the simultaneous operation of an **M.2 NVMe SSD**, in 2280, 2260, 2242 and 2230 format, and a **2.5" or 3.5" SATA HDD or SSD** through the USB interface.

Clone Function without PC

The built-in **clone function** allows to clone memory without using a PC. It is possible to clone from **NVMe to SATA** and **SATA to NVMe**.



Item no. 64252

EAN: 4043619642526

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 10 Gbps USB Type-C™ female
 - 1 x M.2 key M slot
 - 1 x SATA 6 Gb/s 22 pin receptacle
 - 1 x DC jack
- Chipset: JMicron JMS581D
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- For 2.5" and 3.5" SATA HDD / SSD
- Supports NVM Express (NVMe)
- Supports S.M.A.R.T.
- Supports TRIM
- Supports Native Command Queuing (NCQ)
- Data transfer rate up to 10 Gbps
- Supports UASP
- 7 x LED indicator for power, access and copy status
- Bootable
- Function key:

- 1 x Clone button
 - 1 x On / Off switch
 - 1 x switch for clone mode
 - Dimensions (LxWxH): ca. 107 x 35 x 24 mm
 - Hot Plug, Plug & Play
-

Power supply specification

- Wall power supply
 - Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.5 A
 - Output: 12 V / 3 A
 - Ground outside, plus inside
 - Dimensions:
 - inside: \varnothing ca. 2.5 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 10 mm
-

System requirements

- Android 11.0 or above
 - Chrome OS
 - Linux Kernel 5.15 or above
 - Mac OS 12.4 or above
 - Windows 10/10-64/11
 - iPad Air (4th Generation) or above
 - iPad Pro (3rd Generation) or above
 - Surface Pro 7
 - PC or laptop with a free USB Type-A port or
 - Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port
-

Package content

- USB Type-C™ converter
- Cable USB-C™ male to USB-C™ male, length ca. 80 cm
- Cable USB-C™ male to USB Type-A male, length ca. 80 cm
- 3 x rubber nipple
- External power supply 12.0 V / 3.0 A
- User manual

Images



General

Function:	bootable Clone Function
Suitable for data medium:	2.5" 3.5"
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 12.4 oder höher Android 11.0 or above Linux Kernel 5.15 or above
LED indicator:	7 x
Slot:	PCIe
Supported module:	M.2 modules in format 2280, 2260 and 2242 with key M or key B+M based on PCIe

Interface

Connector 1:	1 x USB 10 Gbps USB Type-C™ female
Connector 2:	1 x SATA 6 Gb/s 22 pin receptacle
connector 3:	1 x 67 pin M.2 key M slot
connector 4:	1 x 12 V DC jack

Technical characteristics

Chipset:	JMicron JMS581D
Data transfer rate:	10 Gbps

Physical characteristics

Colour:	black
---------	-------