

# Delock Active USB Type-C™ to HDMI Adapter 4K 60 Hz (HDR)

### **Description**

This adapter by Delock is suitable for the connection of a HDMI monitor to a computer with USB-C<sup>TM</sup> interface and DisplayPort alternate mode support. The adapter supports a resolution up to 4K Ultra HD at 60 Hz and is backward compatible to Full-HD 1080p.

#### **Active adapter**

The adapter offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.



#### Item no. 65400

EAN: 4043619654000 Country of origin: China Package: Retail Box

#### **Technical details**

- Connectors:
  - 1 x USB Type-CTM male >
  - 1 x HDMI-A female
- Chipset: Parade PS186, Fresco Logic FL7102
- DisplayPort 1.4 and High Speed HDMI specification
- Active converter, for graphics cards with DP and DP++ output
- Signal direction: USB Type-C<sup>TM</sup> input > HDMI output
- · Cable gauge:
  - 32 AWG data line
  - 24 AWG power line
- Cable diameter: ca. 5 mm
- · Connectors: gold-plated
- · Transmission of audio and video signals
- Data transfer rate up to 18 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz
   (depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.3
- 1 x ferrite core



- Cable length without connectors: ca. 20 cm
- · Colour: black

## System requirements

 Device with a free USB Type-C<sup>™</sup> port and DisplayPort alternate mode or with a free Thunderbolt<sup>™</sup> 3 port

## **Package content**

• USB-CTM to HDMI adapter

## **Images**







#### General

Specification: High Speed HDMI HDCP 1.4 DisplayPort 1.4 **HDR HDCP 2.3** 

## Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x HDMI-A female

#### **Technical characteristics**

Chipset:	Fresco Logic FL7102 Parade PS186
Data transfer rate:	18 Gbps
Maximum screen resolution:	3840 x 2160 @ 60 Hz

## **Physical characteristics**

Ferrite core:	1 x
Cable length:	20 cm
Pin finishing:	gold-plated
Conductor gauge:	32 AWG data line 24 AWG power line
Colour:	grey / black
Cable diameter:	5 mm