

# Delock Professional USB Condenser Microphone Set for Podcasting and Gaming

## Description

This professional USB condenser microphone by Delock can be used for high-quality voice and vocal recordings.

### Optimal recordings

The microphone has a 16 mm condenser and a cardioid polar pattern (unidirectional) and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

### Dual Layer Pop Filter & Windscreen

Due to the included dual layer pop filter and the windscreen, the recording quality is further optimized. Annoying wind noises are optimally filtered.

### High sampling rate

Typical USB microphones work with 16 Bit and 44 KHz. The Delock microphone offers a sampling rate of 24 Bit and 192 kHz, so it is possible to record in Hi-Fi studio quality.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

### Stable & adjustable stand

The stand ensures that the microphone is stable on the table. With the telescopic function, the microphone can be adjusted to the preferred height.



**Item no. 66300**

EAN: 4043619663002

Country of origin: China

Package: Retail Box

## Technical details

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional

- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA
- Sound pressure level (SPL): max. 120 dB
- Dual-Layer pop filter: Ø 120 mm
- Stand: Ø ca. 130 mm (ca. 600 g)
- USB bus powered
- Plug & Play

---

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

---

## Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable, length ca. 2.5 m
- Shock mount (spider)
- Telescopic rod
- Stand
- Pop filter
- Windscreen
- User manual

---

## Images



## General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.10 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

## Technical characteristics

Frequency range:	30 Hz - 16 kHz
Voltage:	USB bus powered
Sensibility:	-38 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	uni-directional

## Physical characteristics

Cable length:	2.5 m
Colour:	black