

# Delock DIP switch Tri-State 9-digit 2.54 mm pitch THT vertical black 2 pieces

## Description

This DIP switch by Delock is suitable for the solder mounting on a PCB.

### Tri-State circuit

The tri-state switch consists of 9 single switches, each with 3 switching positions (+, 0, -) per position. This allows to set more codings than a standard DIP switch with only 2 switch positions (on / off).

### THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

### Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



2 x

**Item no. 66309**

EAN: 4043619663095

Country of origin: China

Package: Tube

## Technical details

- Connectors:
  - 1 x 11 soldering pin
- Number of positions: 9
- Pitch: 2.54 mm
- Switch positions: 3 (+, 0, -)
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 1000 MΩ / 500 VDC
- Withstanding voltage: 500 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -30 °C ~ 85 °C
- Material: plastic
- Colour: black

- Dimensions (LxWxH): ca. 24.3 x 7.0 x 3.8 mm

---

## Package content

- 2 x DIP switch

---

## Images



### General

Mounting type:	Soldering
----------------	-----------

### Interface

connector:	1 x 11 soldering pin
------------	----------------------

### Technical characteristics

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-30 °C ~ 85 °C
Resistor:	1000 MΩ / 500 VDC

### Physical characteristics

Pitch distance:	2.54 mm
Material:	Plastic
Length:	24.3 mm
Width:	7.0 mm
Height:	3.8 mm
Colour:	black