

Delock USB Condenser Microphone with Stand 24 Bit / 192 kHz for PC and Laptop

Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recording, making it suitable for **streaming, podcasting, gaming** and **video meetings**.

Optimal recordings

The microphone has a **cardioid polar pattern (unidirectional)** and captures the sound ideally. Due to a high performance, low self-noise and precise reproduction, even the finest sounds are optimally recorded.

High resolution sampling rate

Typical USB microphones work with 16 Bit and 44 kHz. The Delock microphone offers a sampling rate of **24 Bit** and **192 kHz**, so that recordings in **high-resolution HiFi studio quality** are possible.

Stepless microphone gain

The microphone gain control allows you to individually increase or decrease the volume of the microphone recording.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows, Mac OS, Chrome OS** and **Linux**.

Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The tripod table stand can be folded and transported easily if required.



Item no. 66832

EAN: 4043619668328

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional

- Sensitivity: -13 dB +/- 3 dB
- Frequency range: 20 Hz - 20 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Sound pressure level (SPL): max. 93 dB
- Cable length: ca. 1.5 m
- USB bus powered
- Plug & Play


System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable
- Table stand (tripod)
- Microphone installation ring
- User manual

Images



General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

connector:	1 x USB 2.0 Type-A male 1 x USB 2.0 Type-B male
Input:	1 x USB 2.0 Type-B female

Technical characteristics

Frequency range:	20 Hz - 20 kHz
Voltage:	USB bus powered
Sensibility:	- 13 dB +/- 3 dB
Sample rate:	24 Bit / 176 kHz
Signal noise ratio (SNR):	ca. 60 dB
Directivity:	uni-directional

Physical characteristics

Cable length:	1.5 m
Colour:	black