

Delock Adapter D-Sub 9 pin male with nuts to D-Sub 25 pin female with screws

Description

This narrow adapter by Delock can, for example, connect devices such as printers, modems and computers with serial RS-232 D-Sub 9 or D-Sub 25 interfaces.



Item no. 66982

EAN: 4043619669820

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x D-Sub 9 pin male with nuts
 - 1 x D-Sub 25 pin female with screws
- Pin assignment: 1 – 8, 2 – 3, 3 – 2, 4 – 20, 5 – 7, 6 – 6, 7 – 4, 8 – 5, 9 – 22, shielded
- Contacts: gold plated brass
- Screw type: #4-40 UNC
- Dimensions (LxWxH): ca. 53 x 18 x 13 mm

System requirements

- A free D-Sub 9 pin interface
- A free D-Sub 25 pin interface

Package content

- Adapter D-Sub 9 pin to D-Sub 25 pin

Images

| DB 9 Pin | Name | DB 25 Pin |
|----------|------|-----------|
| 1 | DCD | 8 |
| 2 | RXD | 3 |
| 3 | TXD | 2 |
| 4 | DTR | 20 |
| 5 | GND | 7 |
| 6 | DSR | 6 |
| 7 | RTS | 4 |
| 8 | CTS | 5 |
| 9 | RI | 22 |

Interface

| | |
|--------------|--|
| Connector 1: | 1 x Serial D-Sub 9 male with nuts |
| Connector 2: | 1 x Serial D-Sub 25 female with screws |

Technical characteristics

| | |
|----------------------|--|
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |
|----------------------|--|

Physical characteristics

| | |
|----------------|-----------------|
| Pin finishing: | gold-plated |
| Screw type: | #4-40 UNC |
| Material: | metal / plastic |
| Length: | 53 mm |
| Width: | 18 mm |
| Height: | 13 mm |
| Colour: | silver / orange |