

# Delock Z-Wave® Power Switch

## Description

This Delock power switch is compatible to the Z-Wave® standard and can be connected to a Z-Wave® Gateway smoothly. By the help of a Gateway or software (APP) the socket can be switched on or off.



**Item no. 78010**

EAN: 4043619780105

Country of origin: China

Package: White Box

## Technical details

- Z-Wave® compatible power switch
- Frequency: 868.42 MHz
- Z-Wave® 500 series
- CEE 7/4 (male) und CEE 7/3 (female) (type-F)
- Voltage area: 220 ~ 240 V
- Max. load: 2500 W
- Max. current: 11 A
- 1 x inclusion / exclusion button
- 1 x LED indicator
- Suitable for interior use
- Power consumption:
  - Operating: 0.005 mA
  - Sleeping mode: 0.001 mA
- Operating distance: ca. 30 m
- Operating temperature: 0 ~ 40 °C
- Dimension (LxWxH): ca. 105 x 76 x 62 mm

## System requirements

- Z-Wave® Gateway

---

## Package content

- Z-Wave® power switch
- User manual

---

## Images



## General

Suitable for indoor:	yes
LED indicator:	1 x

## Technical characteristics

Frequency range:	Z-Wave 868.42 MHz
Operating temperature:	0 °C ~ 40 °C
Maximum load:	2500 W
Maximum current:	11 A
Operating range:	ca. 30 m
Voltage area:	220 ~ 240 V
Current consumption:	Operating: 0.005 mA Sleeping mode: 0.001 mA

## Physical characteristics

Length:	105 mm
Width:	76 mm
Height:	62 mm