

Delock Z-Wave® RGBW LED Controller

Description

This Delock LED controller is compatible to the Z-Wave® standard and can be connected to a Z-Wave® Gateway smoothly. The controller can be used to control e.g. LED stripes or light stripes.



Item no. 78011

EAN: 4043619780112

Country of origin: China

Package: White Box

Technical details

- Z-Wave® compatible RGBW LED controller
- Frequency: 868.42 MHz
- Z-Wave® 500 series
- Input voltage = output voltage: 12 V or 24 V
- Max. 13 A output
- 1 x inclusion / exclusion button
- 1 x LED indicator
- Suitable for interior use
- Power consumption:
 - at 12 V: 0.04 A
 - at 24 V: 0.03 A
- Operating distance: ca. 30 m
- Operating temperature: 0 ~ 40 °C
- Dimension (LxWxH): ca. 41.2 x 33.0 x 14.5 mm


System requirements

- Z-Wave® Gateway

Package content

- Z-Wave® RGBW LED controller
- User manual

Images



General

Suitable for indoor:	yes
LED indicator:	1 x

Technical characteristics

Frequency range:	Z-Wave 868.42 MHz
Operating temperature:	0 °C ~ 40 °C
Maximum current:	13 A
Operating range:	ca. 30 m
Voltage area:	12 V or 24 V
Current consumption:	At 12 V: 0.04 A At 24 V: 0.03 A

Physical characteristics

Length:	41.2 mm
Width:	33 mm
Height:	14.5 mm