

Delock M12 Cable A-coded 8 pin male to male PVC 2 m

Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.



2 m

Item no. 80807

EAN: 4043619808076

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x M12 male A-coded 8 pin
 - 1 x M12 male A-coded 8 pin
- Cat.5e specification
- S/FTP
- Shielding: aluminium foil, tinned copper braiding
- Copper conductor
- Cable gauge: 24 AWG (0.205 mm²)
- Cable diameter: ca. 6 mm
- Cable jacket material: PVC
- Rated current: 2 A / 30 V
- Operating temperature: -25 °C ~ 80 °C
- Protection class: IP67
- Colour: black
- Length incl. connectors: ca. 2 m

Package content

- M12 cable

Images



General

| | |
|----------------------|---------|
| Specification: | Cat. 5e |
| Protection category: | IP67 |

Interface

| | |
|--------------|----------------------------|
| Connector 1: | 1 x M12 male A-coded 8 pin |
| Connector 2: | 1 x M12 male A-coded 8 pin |

Technical characteristics

| | |
|------------------------|----------------|
| Operating temperature: | -25 °C ~ 80 °C |
| Maximum current: | 2 A |
| Voltage: | 30 V |

Physical characteristics

| | |
|------------------------|--------|
| Conductor material: | copper |
| Conductor gauge: | 24 AWG |
| Shielding: | S/FTP |
| Length: | 2 m |
| Colour: | black |
| Cable diameter: | 6 mm |
| Cable jacket material: | PVC |