

Delock M12 Cable D-coded 4 pin male to male PVC 1 m

Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.



1 m

Item no. 80847

EAN: 4043619808472

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors: 2 x M12 male D-coded 4 pin
- Cat.5e specification
- S/FTP
- Shielding: aluminium foil, tinned copper braiding
- Copper conductor
- Cable gauge: 26 AWG (0.129 mm²)
- Cable diameter: ca. 5 mm
- Cable jacket material: PVC
- Rated current: 4 A / 60 V
- Operating temperature: -25 °C ~ 60 °C
- Protection class: IP67
- Colour: black
- Length incl. connectors: ca. 1 m

Package content

- M12 cable

Images



General

Specification:	Cat. 5e
Protection category:	IP67

Interface

Connector 1:	1 x M12 male D-coded 4 pin
Connector 2:	1 x M12 male D-coded 4 pin

Technical characteristics

Operating temperature:	-25 °C ~ 60 °C
Maximum current:	4 A
Voltage:	60 V

Physical characteristics

Conductor material:	copper
Conductor gauge:	26 AWG
Shielding:	S/FTP
Length:	1 m
Colour:	black
Cable diameter:	5 mm
Cable jacket material:	PVC