

Delock Passive mini DisplayPort 1.1 to HDMI Cable 0.5 m

Description

This cable by Delock can be used to connect a display with an HDMI port to a PC or a laptop with mini DisplayPort interface.



Item no. 83992

EAN: 4043619839926

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x mini DisplayPort male >
 - 1 x HDMI-A male
- Signal direction: mini DisplayPort input > HDMI output
- Chipset: Parade PS8121E
- DisplayPort 1.1a and High Speed HDMI specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Contacts gold-plated
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Triple shielded cable
- Transmission of audio and video signals
- Data transfer rate up to 10.2 Gbps
- Resolution up to 1920 x 1200 @ 60 Hz
(depending on the system and the connected hardware)
- Colour: black
- Length incl. connectors: ca. 0.5 m

System requirements

- A free mini DisplayPort DP++ female

Package content

- Mini DisplayPort to HDMI cable

Images



General

Specification:	DisplayPort 1.1 High Speed HDMI
----------------	------------------------------------

Interface

connector:	1 x mini DisplayPort 20 pin male 1 x High Speed HDMI-A 19 pin male
------------	---

Technical characteristics

Data transfer rate:	10.2 Gb/s
Maximum screen resolution:	1920 x 1200 @ 60 Hz

Physical characteristics

Cable colour:	black
Cable length incl. connector:	0.5 m
Connector finishing:	gold-plated
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	32 AWG
Shielding:	triple