

Delock Cable mini DisplayPort 1.2 male with screw > DVI male 4K 30 Hz Active 5 m black

Description

This cable by Delock allows the connection of a DVI display via a mini DisplayPort interface. It supports a resolution of up to Ultra HD (4K) and is backwards compatible to Full-HD 1080p. The screw of the mini DisplayPort connector secures the connection and prevents accidental unplugging of the cable.



Item no. 85637

EAN: 4043619856374

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x mini DisplayPort 20 pin male with screw >
 - 1 x DVI 24+1 male with screws
- DVI-D (Single Link), VGA not wired
- Input = mini DisplayPort; Output = DVI
- Screw type: #4-40, thread type UNC, thread class 3A, American Standard Screw
- Chipset: Parade PS176
- DisplayPort 1.2 specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Gold-plated connectors
- Active cable, for graphics cards with DP and DP++ output
- Resolution up to 2560 x 1600 @ 60 Hz / 3840 x 2160 @ 30 Hz / 4096 x 2160 @ 24 Hz (depending on the system and the connected hardware)
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Length incl. connectors (L): ca. 5 m
- Colour: black

- OS independent, no driver installation necessary
-


System requirements

- One free mini DisplayPort female
-

Package content

- Cable mini DisplayPort to DVI
-

Images



General

Specification:	DisplayPort 1.2 HDCP 1.3
----------------	-----------------------------

Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x DVI 24+1 male with screws

Technical characteristics

Chipset:	Parade PS176
Maximum screen resolution:	3840 x 2160 @ 30 Hz 4096 x 2160 @ 24 Hz

Physical characteristics

Ferrite core:	2 x
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Screw type:	#4-40 UNC
Length:	5 m
Colour:	black