

Delock PoweredUSB cable male 24 V to 2 x 4 pin male 1 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to connect a device with 2 x 4 pin port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by IBM, NCR or Hypercom. The cable is used both for data transmission and for power supply of the connected device.



Item no. 85950

EAN: 4043619859504

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x Male 2 x 4 pin
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
 - 26 AWG data line
 - 20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors: ca. 1 m

System requirements

- PC or hub with a free PoweredUSB 24 V female port

- Device with a free 2 x 4 pin female port
-

Package content

- PoweredUSB cable
-

Images



General

Specification:	PoweredUSB
----------------	------------

Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	2 x Mini DIN 4 pin

Technical characteristics

Data transfer rate:	USB 2.0 up to 480 Mb/s
Voltage:	24 V

Physical characteristics

Conductor gauge:	26 AWG data line 20 AWG power line
Shielding:	double
Length:	1 m
Colour:	black