

# Delock USB 2.0 adapter na 1 x Serial RS-422/485

## Opis

Ovaj Delock prilagodnik omogućuje povezivanje serijskog uređaja putem USB Tip-A priključka.



### Predmet br. 87585

EAN: 4043619875856

Zemlja podrijetla: China

Pakiranje: Retail Box

## Tehnički podaci

- Priključak:
  - 1 x USB 2.0 Tip-A, ženski >
  - 1 x serijska muška RS-422/485 DB9
- Skup čipova: FT232HL, SP3078EE
- 1 x DIP sklopka: RS-422/485 radna postavka
- Interna pinska glava: prekidač sklopke kratkospojnika uklj / isklj
- Serijski priključci s maticama za vijke
- Brzina prijenosa podataka do 1 Mbps
- LED indikacije aktivnosti Tx/D / Rx/D
- Automatsko prepoznavanje i prespajanje između RS-422 i RS-485
- ±15 kV ESD zaštita na svim signalnim kontaktima
- Zidna ugradnja integrirana u kućište
- Struja potrošnje:
  - rad: ≤ 61 mA / 305 mW
  - mirovanje: oko 16 mA / 80 mW
- Dodatni I/O i IRQ nisu potrebni
- Radna temperatura: 0 °C ~ 70 °C
- Mjere (DxŠxV): oko 80 x 72 x 23 mm

## Preuvjeti sustava

- Linux Kernel 2.6 ili noviji
- Windows Server 2012/Server 2012 R2/Server 2016
- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom

## Sadržaj pakiranja

- USB 2.0 na 1 x serijski RS-422/485 adapter
- USB 2.0 kabel
- 2 x kratkospojnik
- CD s upravljačkim programom
- Korisnički priručnik

## Slike



Pin	Transmission Signals		
	RS-422	4-Wire RS-485	2-Wire RS-485
1	Tx-	Tx-	D-
2	Tx+	Tx+	D+
3	Rx+	Rx+	
4	Rx-	Rx-	
5	GND	GND	GND

## General

Funkcija:	Converter Programmable EEPROM
Mounting type:	Postavljanje na zid
Tehnički podaci:	RS-422 / RS-485 (EIA / TIA) UHCI/OHCI/EHCI
Supported operating system:	Linux Kernel 2.6 ili noviji Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2012 R2 Windows Server 2016 Windows Server 2019 Windows 11
LED indikator:	RX / TX
Protection:	Failsafe protection for open, shorted or terminated lines
DIP Switches:	2 x

## Interface

Priključak 1:	1 x USB Type-B
Priključak 2:	1 x serijska muška priključka DB9 s maticama za vijke

## Technical characteristics

Skup čipova:	SP3078EE FTDI 232HL
Brzina prijenosa podataka:	RS-422 / RS-485 up to 1 Mbps
FIFO:	1 KByte RX 1 KByte TX
Impedancijaa:	120 Ω

Premosnik:	2 x
Radna temperatura:	0 °C ~ 70 °C
Maximum power consumption:	305 mW
Signal transmission:	Tx+, Tx-, Rx+, Rx-, GND
Data transmission:	asynchronous Bi-directional Poludupleks full duplex differential
Napon:	Napajanje iz USB sabirnice
UART:	USB to serial UART
Otpornik:	Terminalresistor 120 Ω ON/OFF
Support:	256 Multidrop Nodes
Data bits:	7, 8

## Physical characteristics

Feritna jezgra:	1 x
Materijal kućišta:	metal
Boja kabela:	crne
Duljina:	80 mm
Width:	72 mm
Height:	23 mm
Boja:	siv / bijela / plava
Overvoltage protection:	±8 kV EN / IEC 61000-4-2 kontaktno pražnjenje 15 kV RS-422 / RS-485