

# Delock Serijski kabel RS-232 D-Sub 9 ženski/ženski nulti modem s uskim kućištem utikača - CTS / RTS automatsko upravljanje - 1 m

## Opis

Ovaj serijski kabel tvrtke Delock je potpuno žičani nulti modemska kabel – CTS / RTS automatsko upravljanje – za pisače, mjerne instrumente, pretvarače, RS-232 konzentrate, patch panele, itd. Ovim kabelom mogu se spojiti dva serijska RS-232 uređaja međusobno radi razmjene podataka.

### Mini D-Sub 9 konektor

Ovi kabeli pristaju svakom ulazu tipa RS-232, jer su mini D-Sub 9 (44 x 33,3 x 15 mm) spojnici maleni i kompaktni. Tako se RS-232 spojnici mogu koristiti odmah jedan pored drugog.



1 m

### Predmet br. 87786

EAN: 4043619877867

Zemlja podrijetla: China

Pakiranje: Plastična vrećica sa zip zatvaračem

## Tehnički podaci

- Priključak:
  - 1 x serijska ženski D-Sub 9 s vijcima
  - 1 x serijska ženski D-Sub 9 s vijcima
- Presjek kabela: 28 AWG
- Potpuno ožičeni kabel
- Dodjeljivanje pinova: 7+8 – 1, 2 – 3, 3 – 2, 4 – 6, 6 – 4, 5 – 5, 1 – 7+8, oklopljen
- Boja: crno
- Izolator: PVC
- Vrsta vijka: #4-40 UNC
- Promjer kabela: oko 5 mm
- Duljina kabela zajedno s priključkom: oko 1 m

## Preduvjeti sustava

- Slobodan D-Sub 9 muški priključak.


---

## Sadržaj pakiranja

- Kabel

---

## Slike



## General

Tehnički podaci:	RS-232 (EIA / TIA)
Style:	Mini Sub-D9 Nullmodem "RTS / CTS auto control"

## Interface

Priključak 1:	1 x serijska ženski D-Sub 9 s vijcima
Priključak 2:	1 x serijska ženski D-Sub 9 s vijcima

## Technical characteristics

Brzina prijenosa podataka:	up to 921.6 Kbps
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND + Schirmung

## Physical characteristics

Cable type:	AWM Style 2464 28 AWG 80 °C 300 V VW-1
Cable length incl. connector:	1 m
Površinska zaštita kontakata:	pozlaćeni
Conductor material:	Copper tinned
Conductor gauge:	AWG 28
Vrsta vijka:	#4-40 UNC
Shielding:	Aluminum foil
Boja:	crne
Cable jacket material:	PVC
Safety of Flammability:	VW-1