

Delock PCI Express Card to 4 x Serial with voltage supply

Description

The Delock PCI Express card expands your PC by four external serial ports. The serial ports support a voltage of 5 V and 12 V, which can be set through the jumper. Thus you do not require an additional power supply for the connected devices.



Item no. 89306

EAN: 4043619893065

Country of origin: China

Package: Retail Box

Technical details

- Connector:
 - internal:
 - 1 x PCI Express x1, V1.1
 - 1 x power connector 4 pin Molex male
 - external:
 - 1 x DB44 female
- connecting cable: DB44 male > 4 x serial RS-232 DB9 male
- Chipset: Oxford OXPCIe954
- Data transfer rate up to 230.4 Kb/s
- Compatible with 16C950 UART
- FIFO: 128 byte
- ±15KV ESD protection on all signal pins
- 5 V or 12 V voltage can be set individually for each port through the jumper (Pin 1/4/8/9)
- Electrical power per port: 5.5 watt (5 V / 1.1 A)
- Electrical power per port: 13.2 watt (12 V / 1.1 A)
- I/O address and IRQ assigned by BIOS



System requirements

- Windows XP/XP-64/Vista/Vista-64/7/7-64/8/8.1/10/10-64
- PC with one free PCI Express slot
- Power supply with a free Molex power connector

Package content

- PCI Express card
- 1 serial connecting cable
- Low profile bracket
- Driver CD
- User manual

Images



General

Form factor:	Low Profile
Function:	Power over Serial
Specification:	RS-232 (EIA / TIA) PCIe 1.1
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Vista 32-bit Windows Vista 64-bit Windows XP 32-bit Windows XP 64-bit
Slot:	PCIe

Interface

External:	1 x Serial RS-232 DB9 plug
Internal:	1 x PCI Express x1, V1.1

Technical characteristics

Chipset:	Oxford OXPCIe954
Data transfer rate:	4 x up to 230,4 Kbps
FIFO:	4 x 128 Byte
Jumper:	20 x
Maximum current:	1100 mA per port
Voltage:	5 V or 12 V can be set individually for each port through the jumper (pin 1 or 9)
UART:	16C950