


Delock PCI Card > 1 x Serial RS-232 High Speed 921K with Voltage supply

Description

The Delock PCI card expands your system by one High Speed RS-232 port. Use this card for applications like data logging, machine control systems, automation, development or communication. By the extensive surge protection and the wide temperature range this card can be used in the industrial area. Connected devices can be supplied with voltage of 5 V or 12 V optionally.



Item no. 89326

EAN: 4043619893263

Country of origin: Taiwan,
Republic of China

Package: Box

Technical details

- Chipset: Systembase SB16C1052PCI
- Connector:
 - external:
 - 1 x Serial RS-232 D-Sub 9 Pin male
 - internal:
 - 1 x PCI
 - 1 x 4 pin Molex power connector
- Baud rate: up to 921.6 Kb/s
- Compatible to 16C550 UART
- FIFO 256 Byte
- Data bit: 5, 6, 7, 8
- Stop bit: 1, 1.5, 2
- Parity: None, Even, Odd, Space, Mark
- Flow Control: RTS / CTS, XON / XOFF
- Selectable voltage supply 5 V / 12 V or RI of pin 9
- Operating temperature: -30 °C ~ +75 °C
- Storage temperature: -40 °C ~ +85 °C
- Ambient relative humidity max. 95 % (non-condensing)

- 15 kV ESD protection for all signals
 - Bus: universal 32/64 Bit 3.3/5 V PCI version 2.1, 2.2, 2.3 and PCI-X
 - I/O address and IRQ assigned by the system
-

System requirements

- Windows XP/XP-64/Vista/Vista-64/7/7-64, Linux ex Kernel 2.6
 - PC with a free PCI slot
 - Power supply with a free Molex power connector
-

Package content

- PCI card
 - Low profile bracket
 - Driver CD
 - User manual
-

Images

