

Delock LTE / GSM / UMTS antena SMA muški 2 dBi, fiksna, višesmjerna s kabelom za povezivanje (RG-316U, 3 m) vanjska crni

Opis

Ova Delock LTE antena omogućuje vam uporabu različitih LTE opsega na otvorenim i u zatvorenim prostorima. U potpunosti je usklađena za GSM, UMTS, Bluetooth, WLAN 2,4 GHz, ZigBee, DECT, Z-Wave i LoRa 868 MHz / 915 MHz.



Predmet br. 89589

EAN: 4043619895892

Zemlja podrijetla: China

Pakiranje: Retail Box

Tehnički podaci

- Priključak: 1 x SMA muški
- Frekvencijski opseg:
694 - 960 MHz
1710 - 2700 MHz
- GSM, UMTS, Bluetooth, WLAN 2,4 GHz, ZigBee, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Pojačanje antene: 2 dBi
- Impedancija: 50 ohma
- Polarizacija: linearna, vertikalna
- VSWR: 2,0 - 3,0
- Ugradnja vijcima u rupe promjera 12 mm
- Radna temperatura: -10 °C ~ 55 °C
- Materijal kućišta: ABS otporno na UV zrake
- Boja: crno
- Stupanj zaštite: IP67
- Kabel: koaksijalni
- Vrsta kabela: RG-316U

- Boja kabela: transparentna
- Slabljenje kabela: 0,95 dB @ 1 GHz po metru
- Promjer kabela: cca 2,5 mm
- Duljina kabela: oko 3 m
- Mjere (DxŠ): oko 48 x 50 mm



Preduvjeti sustava

- Uređaj sa slobodnim SMA utičnicom

Sadržaj pakiranja

- Antena
- Matica, podloška

Slike



General

Mounting type:	design mounting
Protection category:	IP67

Interface

priključak:	1 x SMA
-------------	---------

Technical characteristics

Frequency range:	1710 - 2700 MHz 694 - 960 MHz
Antenna gain:	2 dBi
Impedancijaa:	50 Ω
Radna temperatura:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2,0 - 3,0

Physical characteristics

Materijal kućišta:	ABS otporno na UV zrake
Cable category:	koaksijalni
Cable type:	RG-316U
Cable attenuation:	0,95 dB @ 1 GHz pro Meter
Boja kabela:	transparentna
Duljina kabela:	3 m (incl. connector)
Diameter:	50 mm
Duljina:	48 mm