

# Delock USB 5 Gbps PCI Express x1 Card to 3 x external Type-A + 2 x external USB Type-C™ female and 1 x internal 19 pin USB pin header male

## Description

This PCI Express card by Delock expands the PC by three external **Type-A** and two external **USB Type-C™** ports as well as one internal 19 pin USB pin header male port. Different USB devices such as USB flash memory, card reader, external enclosure etc. can be connected. A maximum data transfer rate of up to **5 Gbps** can be reached.



**Item no. 90109**

EAN: 4043619901098

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external:
    - 3 x USB 5 Gbps Type-A female
    - 2 x USB 5 Gbps USB Type-C™ female
  - internal:
    - 1 x 19 pin USB 5 Gbps pin header male
    - 1 x SATA 15 pin power connector
    - 1 x PCI Express x1, V2.0
- Chipset: VIA VL805, Genesys Logic GL3510
- Data transfer rate up to 5 Gbps
- Power supply via SATA power connector
- Electrical power per port: max. 4.5 watt (5 V / 900 mA)
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports UASP
- Supports Multiple INs
- Bootable

---

## System requirements

- Linux Kernel 5.15 or above
- Windows 10/10-64/11
- PC with one free PCI Express slot
- Power supply with a free SATA power connector

---

## Package content

- PCI Express card USB 5 Gbps
- User manual

---

## Images



## General

Function:	bootable
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 11 Linux Kernel 5.15 or above

## Interface

External:	2 x USB 5 Gbps USB Type-C™ female 3 x USB 5 Gbps Type-A female
Internal:	1 x PCI Express x1, V2.0 1 x SATA 15 pin power connector 1 x 19 pin USB 5 Gbps pin header male

## Technical characteristics

Chipset:	Genesys Logic GL3510 VIA VL805
Data transfer rate:	5 Gbps