

# Delock WLAN WiFi 6 Antenna RP-SMA plug 4 - 6 dBi directional with magnetic base with tilt joint

## Description

This Wireless LAN antenna by Delock can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals. With the help of the variable inclination of the antenna tilt and the magnetic base, the antenna can be positioned individually.



**Item no. 90297**

EAN: 4043619902972

Country of origin: Taiwan,  
Republic of China

Package: White Box

## Technical details

- Connector: 1 x RP-SMA plug
- With tilting joint, rotatable
- Frequency range:  
2.400 - 2.500 GHz  
5.150 - 5.875 GHz
- Antenna gain:  
4 dBi @ 2.5 GHz  
6 dBi @ 5.7 GHz
- Impedance: 50 Ohm
- VSWR: 2.0
- Polarisation: linear, vertical
- HBW horizontal beamwidth: 80°
- VBW vertical beamwidth: 70°
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS UV resistant
- Cable type: RG-174
- Cable colour: black
- Cable length: ca. 1 m

- Dimensions (LxWxH): ca. 115.5 x 90.0 x 80.0 mm
- 

## System requirements

- Device with a free RP-SMA jack
- 

## Package content

- WLAN antenna
- 

## Images

