

# Delock 3G-SDI Switch 4 in > 1 out

## Description

With this Delock SDI switch, up to four SDI input sources can be connect to one SDI output device, such as an HD-SDI monitor. By pressing a button on the device, it can be switched from one source to another.



**Item no. 93251**

EAN: 4043619932511

Country of origin: China

Package: Box

## Technical details

- Connectors:  
Input:  
4 x BNC female (3G-SDI)  
1 x 5 V DC jack  
Output:  
1 x BNC female (3G-SDI)
- Supported resolution:  
SD 480i, 525i and 625i  
HD 720p 24, 25, 30, 50 and 60 Hz  
HD 1080i 50, 60 Hz  
HD 1080p 24, 25, 30, 50 and 60 Hz
- Configuration and control of the device via RS232 interface
- Robust metal housing
- Power consumption: max. 3 W
- Dimensions (LxWxH): ca. 162 x 82 x 25 mm

## Power supply specification

- Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:  
inside:  $\varnothing$  ca. 2.1 mm  
outside:  $\varnothing$  ca. 5.5 mm  
length: ca. 9 mm

## Package content

- 3G-SDI Switch
- Power supply

## Images

