

# Delock Mini PCIe Converter to 2 x SATA with RAID

#### Description

This converter by Delock expands the system by two SATA ports. When using more than one SATA port, there is the possibility to use different RAID modes.

#### Note

This product provides a chipset-based RAID function. Management and setting of the RAID mode is not possible via the operating system or BIOS. Different diagnostic software is not compatible with this solution.



#### Item no. 95264

EAN: 4043619952649 Country of origin: China Package: Retail Box

#### **Technical details**

# Connectors: 1 x Mini PCIe male

- 2 x SATA 6 Gb/s 7 pin plug
- 1 x 2 pin pin header for LED
- Chipset: Asmedia ASM1061R
- Interface: PCI Express revision 2.0
- Data transfer rate: SATA up to 6 Gb/s PCI Express up to 5 Gb/s
- Supports RAID 0, 1, SPAN
- Supports hard drive with Native Command Queue (NCQ) feature
- Supports SATA Port Multiplier
- Supports S.M.A.R.T.
- Supports TRIM

#### System requirements

- Linux Kernel 3.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11

#### **DATASHEET**



• Motherboard with a free Mini PCIe slot with a PCIe interface

#### Package content

- Mini PCIe module
- Driver CD
- User manual

#### Images







 $\ensuremath{\textcircled{O}}$  2024 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.



#### General

Linux Kernel 3.3 or above
Windows 10 32-Bit
Windows 10 64-Bit
Windows 7 32-Bit
Windows 7 64-Bit
Windows 8.1 32-Bit
Windows 8.1 64-Bit

### Interface

Connector 1:	1 x Mini PCIe male
Connector 2:	2 x SATA 6 Gb/s 7 pin plug
connector 3:	1 x 2 pin pin header for LED

## **Technical characteristics**

Chipset:	Asmedia ASM1061R
RAID function:	SPAN 0 1