

# Delock USB Bluetooth 2.1 + EDR 1 T/R

## Description

The Delock USB module offers in a compact construction Bluetooth 2.1 + EDR function via USB interface and is ideal for application in industry components like sensors, IPCs, notebooks as well as PDAs.



**Item no. 95865**

EAN: 4043619958658

Country of origin: China

Package: Antistatic cover

## Technical details

- USB interface
- Compatible with USB V2.0 full speed (12Mbit/s) and downwards compatible to USB1.1
- Bluetooth specification V1.1, V1.2 , V2.0 and V2.1 + EDR conform
- CSR BlueCore4-ROM (A07)single chip bluetooth system
- Supports full speed class 2 bluetooth operation for 7 devices with full slave-function in a piconet
- Supports onboard single antenna connection mini Coax (optional)
- Printed PCB antenne on board
- LED indicator for bluetooth activity
- Voltage: 3.3V +/- 0.3V
- power input:
  - Idle Mode: 3,3~9mA
  - Operating typical: 55mA
- Operating temperature: 0°~ 70° C
- 28mm x 14mm x 3.9mm (L x W x H) +- 0.15mm
- For windows XP SP2/Vista (IVT BlueSoleil software)

## System requirements

- USB support for integration of the used Hardware

- Windows XP SP2/Vista (IVT BlueSoleil software)
- 

## Package content

- Bluetooth USB Module
- 

## Images

